

Note:

1: Material(材料) :

- Barrel: PhBz (针管: 磷铜)
- Plunger: SK4 (针头: SK4)
- Spring: SWP-B (弹簧: 琴钢线SWP-B)

2: Plating(电镀) :


- Barrel: 2u' Au over 80~120u' Ni (针管: 镀金2u', 镍底80~120u'.)
- Plunger: 80~120u' Ni plated (针头: 镀镍80~120u'.)
- Spring: Gold flash (弹簧: 镀金。)

3: Electrical(电气特性) :

- Rated Current: 1.0A (额定电流: 1.0A)
- Contact Resistance: 150 mohm Max. at working stroke.
- 接触电阻: 最大150毫欧 (在工作行程状态下)

4: Mechanical (机械性能) :

- Force: 45g±20% at 1.35mm stroke (45g±20% 在1.35mm行程状态)。
- Full stroke: 2.00mm (全行程: 2.00mm)
- Durability: 100.000 cycles(min) (寿命: 100000次)



深圳市新富城电子有限公司
Xinfucheng Shenzhen Electronics Co., Ltd.
<http://www.xfcdz.com.cn> TEI: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :				DESIGNED BY:		DWG. NO.	SP1-048120-F02
SHEET:	1 of 1	PROJECTION		LENGTH		ANGLE		CHECKED BY:		TITLE:	测试探针
DATE:	2013.08.22	VER.	D.0	X.XX	±0.05mm	X.XX	±0.50°	APPROVED BY:			
				X.X	±0.10mm	X.X	±1.00°				
				X.	±0.20mm	X.	±2.00°				