


Tip:5x5



Note:

1: Material (材料):

Barrel: Brass (针管: 黄铜)

Plunger: BeCu (针头: 铍铜)

Spring: SUS304 (弹簧: 不锈钢SUS304)

2: Plating (电镀):

Barrel: 6u' Au over 100~140u' Ni (针管: 镀金6u', 镍底100~140u'.)

Plunger: 8u' Au over 80~120u' Ni (针头: 镀金8u', 镍底80~120u'.)

Spring: No plated (弹簧: 不电镀。)

3: Electrical (电气特性):

Rated Current: 1.0A (额定电流: 1.0A)

Contact Resistance: 50 mohm Max. at working stroke.


接触电阻: 最大50毫欧 (在工作行程状态下)

4: Mechanical (机械性能):

Force: 210g±20% at 4.30mm stroke (210g±20% 在4.30mm行程状态)。

Full stroke: 6.50mm (全行程: 6.50mm)

Durability: 200.000 cycles(min) (寿命: 200000次)



深圳市新富城电子有限公司

Xinfucheng Shenzhen Electronics Co., Ltd.

http://www.xfcdz.com.cn TEL: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :				DESIGNED BY:		DWG. NO.	SP1-136340-H02
SHEET:	1 of 1	PROJECTION		LENGTH		ANGLE		CHECKED BY:		TITLE:	测试探针
DATE:	2013.07.26	VER.	D.0	X.XX	±0.05mm	X.XX	±0.50°	APPROVED BY:			
				X.X	±0.10mm	X.X	±1.00°				
				X.	±0.20mm	X.	±2.00°				