





Top



Bottom

Tip Style

F	B	D
		

Unit: Millimeter[inch]

 Pointing accuracy: ± 0.04 mm

- **Minimum Pitch:** 0.75mm [.0295]
- **Operating Temperature:** -55°C to $+155^{\circ}\text{C}$
- **Mechanical Specifications:**
 - Force: 42g[1.4815oz] at 2.00mm[.0787].
 - Recommended stroke: 2.00mm[.0787].
 - Full stroke: 3.15mm[.1240].
 - Mechanical Life: 500,000 cycles.
- **Material and Finishes:**
 - Barrel: Phosphor Bronze /Gold plated
 - Plunger Top: Hardened BeCu /Gold plated
 - Plunger Bottom: Hardened BeCu /Gold plated
 - Spring: Music wire /Gold plated
- **Electrical Specifications:**
 - Rated Current: 1.0A Continuous.
 - Self Inductance: 1.52nH.
 - Bandwidth: 7.45GHz@-1dB.
 - Contact Resistance: Less than 100mohm.
 - Capacitance: 0.81pF.
 - Time Delay: 70 pSec.

All right reserved. No part of this drawing may be copied, reproduced and transmitted in any forms or by any means without written permission of Xinfucheng Shenzhen Electronics Co., Ltd.