

Note:

1: Material (材料):

Barrel: PhBz (针管: 磷铜)

Plunger: SK4 (针头: SK4)

Spring: SWP-B (弹簧: 琴钢线SWP-B)

2: Plating (电镀):

Barrel: 3u' Au over 80~120u' Ni (针管: 镀金3u', 镍底80~120u'.)

Plunger: 80~120u' Ni plated (针头: 镀镍80~120u'.)

Spring: Gold flash (弹簧: 镀金。)

3: Electrical (电气特性):

Rated Current: 1.0A (额定电流: 1.0A)

Contact Resistance: 150 mohm Max. at working stroke.


接触电阻: 最大150毫欧 (在工作行程状态下)

4: Mechanical (机械性能):

Force: 45g±20% at 1.35mm stroke (45g±20% 在1.35mm行程状态)

Full stroke: 2.00mm (全行程: 2.00mm)

Durability: 100.000 cycles(min) (寿命: 100000次)



深圳市新富城电子有限公司

Xinfucheng Shenzhen Electronics Co., Ltd.

http://www.xfcdz.com.cn TEI: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :				DESIGNED BY:	DWG. NO.	SP1-048120-F01
SHEET:	1 of 1	PROJECTION		LENGTH		ANGLE		CHECKED BY:	TITLE:	测试探针
DATE:	2013.05.10	VER.	D.0	X.XX ±0.05mm	X.XX ±0.50°	X.X ±1.00°	APPROVED BY:			
				X.X ±0.10mm	X. ±2.00°					