

Note:

1: Material(材料):

Barrel: PhBz (针管: 磷铜)

Plunger A&B: BeCu (针头A&B: 铍铜)

Spring: SWP-B (弹簧: 琴钢线SWP-B)

2: Plating(电镀):

Barrel: 20u' Au over 30~40u' Ni (针管: 镀金20u', 镍底30~40u'.)

Plunger A&B: 50u' Au over 1~5u' Ni (针头A&B: 镀金50u', 镍底1~5u'.)

Spring: Gold flash (弹簧: 镀金.)

3: Electrical(电气特性):

Rated Current: 0.5A (额定电流: 0.5A)

Contact Resistance: 100 mohm Max. at working stroke.


接触电阻: 最大100毫欧 (在工作行程状态下)

4: Mechanical (机械性能):

Force: 15g $\pm$ 20% at 0.80mm stroke (15g $\pm$ 20% 在0.80mm行程状态)。

Full stroke: 1.10mm (全行程: 1.10mm)

Durability: 100.000 cycles(min) (寿命: 100000次)



深圳市新富城电子有限公司

Xinfucheng Shenzhen Electronics Co., Ltd.

http://www.xfcdz.com.cn TEL: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :				DESIGNED BY:		DWG. NO.	DP4-028072-FD01
SHEET:	1 of 1	PROJECTION		LENGTH		ANGLE		CHECKED BY:		TITLE:	测试探针
DATE:	2013.05.15	VER.	D.0	X.XX	$\pm 0.05\text{mm}$	X.XX	$\pm 0.50^\circ$	APPROVED BY:			
				X.X	$\pm 0.10\text{mm}$	X.X	$\pm 1.00^\circ$				
				X.	$\pm 0.20\text{mm}$	X.	$\pm 2.00^\circ$				