

Note:

1: Material(材料):

Barrel: PhBz (针管: 磷铜)

Plunger A&B: BeCu (针头A&B: 铍铜)

Spring: SWP-B (弹簧: 琴钢线SWP-B)

2: Plating(电镀):

Barrel: 20~60u' Au over 60~100u' Ni (针管: 镀金20~60u', 镍底60~100u'.)

Plunger A&B: 40~60u' Au over 80~120u' Ni (针头A&B: 镀金40~60u', 镍底80~120u'.)

Spring: Gold flash (弹簧: 镀金。)

3: Electrical(电气特性):

Rated Current: 0.5A (额定电流: 0.5A)

Contact Resistance: 100 mohm Max. at working stroke.


接触电阻: 最大100毫欧 (在工作行程状态下)

4: Mechanical(机械性能):

Force: 14g±20% at 1.90 mm stroke (14g±20% 在1.90mm行程状态)。

Full stroke: 2.84mm (全行程: 2.84mm)

Durability: 100.000 cycles(min) (寿命: 100000次)



深圳市新富城电子有限公司
Xinfucheng Shenzhen Electronics Co., Ltd.
http://www.xfcdz.com.cn TEI: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :				DESIGNED BY:		DWG. NO.	DP1-035108-DD01
SHEET:	1 of 1	PROJECTION		LENGTH		ANGLE		CHECKED BY:		TITLE:	测试探针
DATE:	2013.06.05	VER.	D.0	X.XX	±0.05mm	X.XX	±0.50°	APPROVED BY:			
				X.X	±0.10mm	X.X	±1.00°				
				X.	±0.20mm	X.	±2.00°				