

Note:

1: Material(材料) :

Barrel: PhBz (针管: 磷铜)

Plunger: SK4 (针头: SK4)

Spring: SUS304 (弹簧: SUS304)

2: Plating(电镀) :

Barrel: 2u' Au over 80~120u' Ni (针管: 镀金2u', 镍底80~120u'.)

Plunger: 80~120u' Ni plated (针头: 镀镍80~120u'.)

Spring: No plated (弹簧: 不电镀。)

3: Electrical(电气特性) :

Rated Current: 1.0 A (额定电流: 1.0 A)

Contact Resistance: 50 mohm Max. at working stroke.


接触电阻: 最大50毫欧 (在工作行程状态下)

4: Mechanical (机械性能) :

Force: 45g±20% at 1.20mm stroke (45g±20% 在1.20mm行程状态)。

Full stroke: 2.00mm (全行程: 2.00mm)

Durability: 100.000 cycles(min) (寿命: 100000次)



深圳市新富城电子有限公司

Xinfucheng Shenzhen Electronics Co., Ltd.

http://www.xfcdz.com.cn TEI: 0755-81739711

SCALE:	N/A	UNIT	mm
SHEET:	1 of 1	PROJECTION	
DATE:	2013.06.19	VER.	D.0

THE UNMARKED TOLERANCE ARE AS BELOW :			
LENGTH		ANGLE	
X.XX	±0.05mm	X.XX	±0.50°
X.X	±0.10mm	X.X	±1.00°
X.	±0.20mm	X.	±2.00°

DESIGNED BY:		DWG. NO.	SP1-058166-E01
CHECKED BY:		TITLE:	测试探针
APPROVED BY:			