


**Tip Style**

F	B	D	T
G	S	A	

Unit: Millimeter[inch]

Pointing accuracy: ±0.04mm

- **Minimum Pitch:** 0.65mm [.0256]
- **Operating Temperature:** -55°C to +155°C
- **Mechanical Specifications:**  
 Force: 28g[.9877oz] at 1.13mm[.0445].  
 Recommended stroke: 1.13mm[.0445].  
 Full stroke: 1.33mm[.0524].  
 Mechanical Life: 500,000 cycles.
- **Material and Finishes:**  
 Barrel: Phosphor Bronze /Gold plated  
 Plunger Top: Hardened BeCu /Gold plated  
 Plunger Bottom: Hardened BeCu /Gold plated  
 Spring: Stainless steel /Gold plated
- **Electrical Specifications:**  
 Rated Current: 1.0A Continuous.  
 Self Inductance: 0.84nH.  
 Bandwidth: 29.55GHz@-1dB.
- **Electrical Specifications:**  
 Contact Resistance: Less than 100mohm.  
 Capacitance: 1.11pF.  
 Time Delay: 69 pSec.

All right reserved. No part of this drawing may be copied, reproduced and transmitted in any forms or by any means without written permission of Xinfucheng Shenzhen Electronics Co., Ltd.