


**Note:**

- 1: Material(材料) :  
 Barrel: PhBz (针管: 磷铜)  
 Plunger A&B: BeCu (针头A&B: 铍铜C1751)  
 Spring: SWP-B (弹簧: SWP-B)
- 2: Plating(电镀) :  
 Barrel: 10u' Au over 80~120u' Ni (针管: 镀金10u', 镍底80~120u'.)  
 Plunger A&B: 10u' Au over 80~120u' Ni (针头A&B: 镀金10u', 镍底80~120u'.)  
 Spring: 1u' Au over 80~120u' Ni (弹簧: 镀金1u', 镍底80~120u'.)
- 3: Electrical(电气特性) :  
 Rated Current & Voltage: DC 12V; 1A (额定电压&电流: 直流12V, 1A)  
 Contact Resistance: 100 mohm Max. at working stroke.  
 接触电阻: 最大100毫欧 (在工作行程状态下)
- 4: Mechanical (机械性能) :  
 Force: 20g±20% at 0.45mm stroke. (20g±20% 在0.45mm行程).  
 Full stroke: 1.20 mm (全行程: 1.20mm)  
 Durability: 200.000 cycles(min) (寿命: 200000次)



深圳市新富城电子有限公司  
 Xinfucheng Shenzhen Electronics Co., Ltd.  
<http://www.xfcdz.com.cn> TEI: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :				DESIGNED BY:		DWG. NO.	DP1-038057-DB01
SHEET:	1 of 1	PROJECTION		LENGTH		ANGLE		CHECKED BY:		TITLE:	测试探针
DATE:	2013.01.19	VER.	D.0	X.XX	±0.05mm	X.XX	±0.50°	APPROVED BY:			
				X.X	±0.10mm	X.X	±1.00°				
				X.	±0.20mm	X.	±2.00°				