

Note:

1: Material(材料) :

Barrel: PhBz (针管: 磷铜)

Plunger: SK4 (针头: SK4)

Spring: SUS304 (弹簧: 不锈钢SUS304)

2: Plating(电镀) :

Barrel: 3u' Au over 80~120u' Ni (针管: 镀金3u', 镍底80~120u'.)

Plunger: 80~120u' Ni plated (针头: 镀镍80~120u'.)

Spring: No plated (弹簧: 不电镀。)

3: Electrical(电气特性) :

Rated Current & Voltage: DC 12V; 0.5A (额定电压&电流: 直流12V, 0.5A)

Contact Resistance: 180 mohm Max. at working stroke.


接触电阻: 最大180毫欧 (在工作行程状态下)

4: Mechanical (机械性能) :

Force: 30g±20% at 1.35mm working stroke (30g±20% 在1.35mm工作行程状态)。

Full stroke: 2.00mm (全行程: 2.00mm)

Durability: 100.000 cycles(min) (寿命: 100000次)



深圳市新富城电子有限公司

Xinfucheng Shenzhen Electronics Co., Ltd.

http://www.xfcdz.com.cn TEL: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :				DESIGNED BY:		DWG. NO.	SP1-038120-D02
SHEET:	1 of 1	PROJECTION		LENGTH		ANGLE		CHECKED BY:		TITLE:	测试探针
DATE:	2013.05.09	VER.	D.0	X.XX	±0.05mm	X.XX	±0.50°	APPROVED BY:			
				X.X	±0.10mm	X.X	±1.00°				
				X.	±0.20mm	X.	±2.00°				