

Note:

1: Material(材料):

Barrel: PhBz (针管: 磷铜)

Plunger A&B: BeCu (针头A&B: 铍铜)

Spring: SWP-B (弹簧: 琴钢线SWP-B)

2: Plating(电镀):

Barrel: 20~60u' Au over 60~100u' Ni (针管: 镀金20~60u', 镍底60~100u'.)

Plunger A&B: 40~60u' Au over 80~120u' Ni (针头A&B: 镀金40~60u', 镍底80~120u'.)

Spring: Gold flash (弹簧: 镀金。)

3: Electrical(电气特性):

Rated Current: 1.0 A (额定电流: 1.0 A)

Contact Resistance: 100 mohm Max. at working stroke.

接触电阻: 最大100毫欧 (在工作行程状态下)

4: Mechanical (机械性能):


Force: 40g±20% at 0.65mm stroke (40g±20% 在0.65mm行程状态)。

Full stroke: 0.90mm (全行程: 0.90mm)

Durability: 100.000 cycles(min) (寿命: 100000次)

物料清单

料件名称	料号
针管	B01-067032-DP
针头A	P01-048017-BE
针头B	P01-067008-FE
弹簧	S-045024-W07013



深圳市新富城电子有限公司
Xinfucheng Shenzhen Electronics Co., Ltd.
http://www.xfcdz.com.cn TEI: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :		DESIGNED BY:		DWG. NO.	DP4-067044-BF01
SHEET:	1 of 1	PROJECTION		LENGTH	ANGLE	CHECKED BY:		TITLE:	测试探针
DATE:	2013.08.03	VER.	D.2	X.XX ±0.05mm	X.XX ±0.50°	APPROVED BY:			
				X.X ±0.10mm	X.X ±1.00°				
				X. ±0.20mm	X. ±2.00°				