

Note:

1: Material(材料):

Barrel: PhBz (针管: 磷铜)  
 Plunger: steel SK4 (针头: SK4)  
 Spring: SWP-B (弹簧: SWP-B)

2: Plating(电镀):


Barrel: 2u' Au over 80~120u' Ni (针管: 镀金2u', 镍底80~120u'.)  
 Plunger: 2u' Au over 80~120u' Ni (针头: 镀金2u', 镍底80~120u'.)  
 Spring: 1u' Au over 80~120u' Ni(弹簧: 镀金1u', 镍底80~120u'.)

3: Electrical(电气特性):

Rated Current & Voltage: DC 12V; 0.5A (额定电压&电流: 直流12V, 0.5A)  
 Contact Resistance: 100 mohm Max. at working stroke.  
 接触电阻: 最大100毫欧(在工作行程状态下)

4: Mechanical (机械性能):

Force: 40g±20% at 2.00mm stroke. (40g±20% 在2.00mm行程).  
 Full stroke: 2.00 mm (全行程: 2.00mm)  
 Durability: 200.000 cycles(min) (寿命: 200000次)



深圳市新富城电子有限公司  
 Xinfucheng Shenzhen Electronics Co., Ltd.  
<http://www.xfcdz.com.cn> TEI: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :				DESIGNED BY:		DWG. NO.	SP1-038120-F02
SHEET:	1 of 1	PROJECTION		LENGTH		ANGLE		CHECKED BY:		TITLE:	测试探针
DATE:	2013.05.22	VER.	D.1	X.XX	±0.05mm	X.XX	±0.50°	APPROVED BY:			
				X.X	±0.10mm	X.X	±1.00°				
				X.	±0.20mm	X.	±2.00°				