


Note:

- 1: Material(材料):
  - Barrel: PhBz (针管: 磷铜)
  - Plunger: SK4 (针头: SK4)
  - Spring: SWP-B (弹簧: 琴钢线SWP-B)
- 2: Plating(电镀):
  - Barrel: 3u' Au over 80~120u' Ni (针管: 镀金3u', 镍底80~120u'.)
  - Plunger: 80~120u' Ni plated (针头: 镀镍80~120u'.)
  - Spring: Gold flash (弹簧: 镀金。)
- 3: Electrical(电气特性):
  - Rated Current: 1.0A (额定电流: 1.0A)
  - Contact Resistance: 150 mohm Max. at working stroke.  
接触电阻: 最大150毫欧 (在工作行程状态下)
- 4: Mechanical (机械性能):
  - Force: 15g±20% at 1.50mm stroke (15g±20% 在1.50mm行程状态)。
  - Full stroke: 1.50mm (全行程: 1.50mm)
  - Durability: 100.000 cycles(min) (寿命: 100000次)



深圳市新富城电子有限公司  
Xinfucheng Shenzhen Electronics Co., Ltd.  
<http://www.xfcdz.com.cn> TEL: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :		DESIGNED BY:		DWG. NO.	SP1-048115-D01
SHEET:	1 of 1	PROJECTION		LENGTH	ANGLE	CHECKED BY:		TITLE:	测试探针
DATE:	2013.06.27	VER.	D.0	X.XX ±0.05mm X.X ±0.10mm X. ±0.20mm	X.XX ±0.50° X.X ±1.00° X. ±2.00°	APPROVED BY:			