

Note:

1: Material(材料):

Barrel: PhBz (针管: 磷铜)
 Plunger: SK4 (针头: SK4)
 Spring: SWP-B (弹簧: 琴钢线SWP-B)

2: Plating(电镀):


Barrel: 3u' Au over 80~120u' Ni (针管: 镀金3u', 镍底80~120u'.)
 Plunger: 80~120u' Ni plated (针头: 镀镍80~120u'.)
 Spring: Gold flash (弹簧: 镀金.)

3: Electrical(电气特性):

Rated Current: 1.0A (额定电流: 1.0A)
 Contact Resistance: 150 mohm Max. at working stroke.
 接触电阻: 最大150毫欧 (在工作行程状态下)

4: Mechanical (机械性能):

Force: 15g \pm 20% at 1.50mm stroke (15g \pm 20% 在1.50mm行程状态)。
 Full stroke: 1.50mm (全行程: 1.50mm)
 Durability: 100.000 cycles(min) (寿命: 100000次)



深圳市新富城电子有限公司
 Xinfucheng Shenzhen Electronics Co., Ltd.
<http://www.xfcdz.com.cn> TEL: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :		DESIGNED BY:		DWG. NO.	SP1-048115-D01
SHEET:	1 of 1	PROJECTION		LENGTH	ANGLE	CHECKED BY:		TITLE:	测试探针
DATE:	2013.06.27	VER.	D.0	X.XX \pm 0.05mm X.X \pm 0.10mm X. \pm 0.20mm	X.XX \pm 0.50° X.X \pm 1.00° X. \pm 2.00°	APPROVED BY:			