


Top



Bottom

**Tip Style**

F	B	D	T
G	S	A	

Unit: Millimeter[inch]

Pointing accuracy: ±0.04mm

- **Minimum Pitch:** 0.65mm [.0256]
  - **Operating Temperature:** -55°C to +155°C
  - **Mechanical Specifications:**  
 Force: 35g[1.2346oz] at 1.70mm[.0669].  
 Recommended stroke: 1.70mm[.0669].  
 Full stroke: 2.50mm[.0984].  
 Mechanical Life: 500,000 cycles.
  - **Material and Finishes:**  
 Barrel: Phosphor Bronze /Gold plated  
 Plunger Top: Hardened BeCu /Gold plated  
 Plunger Bottom: Hardened BeCu /Gold plated  
 Spring: Music wire /Gold plated
  - **Electrical Specifications:**  
 Rated Current: 1.0A Continuous.  
 Self Inductance: 1.52nH.  
 Bandwidth: 7.45GHz@-1dB.
- Contact Resistance: Less than 100mohm.  
 Capacitance: 0.81pF.  
 Time Delay: 70 pSec.

All right reserved. No part of this drawing may be copied, reproduced and transmitted in any forms or by any means without written permission of Xinfucheng Shenzhen Electronics Co., Ltd.