


Note:

- 1: Material(材料) :
 - Barrel: PhBz (针管: 磷铜)
 - Plunger: SK4 (针头: SK4)
 - Spring: SUS304 (弹簧: 不锈钢SUS304)
- 2: Plating(电镀) :
 - Barrel: 3u' Au over 80~120u' Ni (针管: 镀金3u', 镍底80~120u'.)
 - Plunger: 80~120u' Ni plated (针头: 镀镍80~120u'.)
 - Spring: No plated (弹簧: 不电镀。)
- 3: Electrical(电气特性) :
 - Rated Current & Voltage: DC 12V; 0.5A (额定电压&电流: 直流12V, 0.5A)
 - Contact Resistance: 180 mohm Max. at working stroke.
 - 接触电阻: 最大180毫欧 (在工作行程状态下)
- 4: Mechanical (机械性能) :
 - Force: 30g±20% at 1.35mm working stroke (30g±20% 在1.35mm工作行程状态下)
 - Full stroke: 2.00mm (全行程: 2.00mm)
 - Durability: 200.000 cycles(min) (寿命: 200000次)



深圳市新富城电子有限公司
Xinfucheng Shenzhen Electronics Co., Ltd.
http://www.xfcdz.com.cn TEL: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :		DESIGNED BY:		DWG. NO.	SP1-038120-F01
SHEET:	1 of 1	PROJECTION		LENGTH	ANGLE	CHECKED BY:		TITLE:	测试探针
DATE:	2013.05.08	VER.	D.0	X.XX ±0.05mm	X.XX ±0.50°	APPROVED BY:			
				X.X ±0.10mm	X.X ±1.00°				
				X. ±0.20mm	X. ±2.00°				