

Note:

1: Material (材料):

Barrel: PhBz (针管: 磷铜)
 Plunger A&B: BeCu (针头A&B: 铍铜)
 Spring: SWP-B (弹簧: 琴钢线SWP-B)

2: Plating (电镀):


Barrel: 20u' Au over 80~120u' Ni (针管: 镀金20u', 镍底80~120u'.)
 Plunger A&B: 30u' Au over 80~120u' Ni (针头A&B: 镀金30u', 镍底80~120u'.)
 Spring: Gold flash (弹簧: 镀金.)

3: Electrical (电气特性):

Rated Current: 0.5A (额定电流: 0.5A)
 Contact Resistance: 50 mohm Max. at working stroke.
 接触电阻: 最大50毫欧 (在工作行程状态下)

4: Mechanical (机械性能):

Force: 30g ± 20% at 0.65mm stroke (30g ± 20% 在0.65mm行程状态).
 Full stroke: 1.00mm (全行程: 1.00mm)
 Durability: 300.000 cycles (min) (寿命: 300000次)



深圳市新富城电子有限公司
 Xinfucheng Shenzhen Electronics Co., Ltd.
<http://www.xfcdz.com.cn> TEL: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :				DESIGNED BY:	DWG. NO.	DP1-058057-FD01
SHEET:	1 of 1	PROJECTION		LENGTH		ANGLE		CHECKED BY:	TITLE:	测试探针
DATE:	2013.06.18	VER.	D.0	X.XX	±0.05mm	X.XX	±0.50°	APPROVED BY:		
				X.X	±0.10mm	X.X	±1.00°			
				X.	±0.20mm	X.	±2.00°			