

Note:

1: Material (材料) :

Barrel: PhBz (针管: 磷铜)

Plunger: BeCu (针头: 铍铜)

Spring: SWP-B (弹簧: 琴钢线SWP-B)

2: Plating (电镀) :

Barrel: 5u' Au over 80~120u' Ni (针管: 镀金5u', 镍底80~120u'.)

Plunger: 5u' Au over 80~120u' Ni (针头: 镀金5u', 镍底80~120u'.)

Spring: Gold flash (弹簧: 镀金。)

3: Electrical (电气特性) :

Rated Current: 1.0A (额定电流: 1.0A)

Contact Resistance: 100 mohm Max. at working stroke.


接触电阻: 最大100毫欧 (在工作行程状态下)

4: Mechanical (机械性能) :

Force: 50g±20% at 1.20mm stroke (50g±20% 在1.20mm行程状态)。

Full stroke: 1.90mm (全行程: 1.90mm)

Durability: 100.000 cycles(min) (寿命: 100000次)



深圳市新富城电子有限公司

Xinfucheng Shenzhen Electronics Co., Ltd.

http://www.xfcdz.com.cn TEL: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :		DESIGNED BY:		DWG. NO.	SP1-048090-F01
SHEET:	1 of 1	PROJECTION		LENGTH	ANGLE	CHECKED BY:		TITLE:	测试探针
DATE:	2013.06.18	VER.	D.0	X.XX ±0.05mm X.X ±0.10mm X. ±0.20mm	X.XX ±0.50° X.X ±1.00° X. ±2.00°	APPROVED BY:			