


Note:

- 1: Material(材料) :
 Barrel: PhBz (针管: 磷铜)
 Plunger: BeCu (针头: 铍铜)
 Spring: SWP-B (弹簧: 琴钢线)
- 2: Plating(电镀) :
 Barrel: 3u' Au over 80~120u' Ni (针管: 镀金3u', 镍底80~120u'.)
 Plunger: 80~120u' Ni plated (针头: 镀镍80~120u'.)
 Spring: Gold flash (弹簧: 镀金.)
- 3: Electrical(电气特性) :
 Rated Current & Voltage: DC 12V; 0.5A (额定电压&电流: 直流12V, 0.5A)
 Contact Resistance: 180 mohm Max. at working stroke.
 接触电阻: 最大180毫欧 (在工作行程状态下)
- 4: Mechanical (机械性能) :
 Force: 30g±20% at 1.60mm working stroke (30g±20% 在1.60mm工作行程状态)。
 Full stroke: 2.50mm (全行程: 2.50mm)
 Durability: 100.000 cycles(min) (寿命: 100000次)



深圳市新富城电子有限公司
 Xinfucheng Shenzhen Electronics Co., Ltd.
<http://www.xfcdz.com.cn> TEL: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :				DESIGNED BY:		DWG. NO.	SP1-038140-D01
SHEET:	1 of 1	PROJECTION		LENGTH		ANGLE		CHECKED BY:		TITLE:	测试探针
DATE:	2013.09.12	VER.	D.0	X.XX	±0.05mm	X.XX	±0.50°	APPROVED BY:			
				X.X	±0.10mm	X.X	±1.00°				
				X.	±0.20mm	X.	±2.00°				