

Note:

1: Material(材料):

Barrel: PhBz (针管: 磷铜)
 Plunger: BeCu (针头: 铍铜)
 Spring: SWP-B (弹簧: 琴钢线SWP-B)

2: Plating(电镀):


Barrel: 5u' Au over 80~120u' Ni (针管: 镀金5u', 镍底80~120u'.)
 Plunger: 5u' Au over 80~120u' Ni (针头: 镀金5u', 镍底80~120u'.)
 Spring: Gold flash (弹簧: 镀金。)

3: Electrical(电气特性):

Rated Current: 1.0A (额定电流: 1.0A)
 Contact Resistance: 100 mohm Max. at working stroke.
 接触电阻: 最大100毫欧 (在工作行程状态下)

4: Mechanical(机械性能):

Force: 50g±20% at 1.20mm stroke (50g±20% 在1.20mm行程状态).
 Full stroke: 1.90mm (全行程: 1.90mm)
 Durability: 100.000 cycles(min) (寿命: 100000次)



深圳市新富城电子有限公司
 Xinfucheng Shenzhen Electronics Co., Ltd.
<http://www.xfcdz.com.cn> TEL: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :		DESIGNED BY:		DWG. NO.	SP1-048090-F02
SHEET:	1 of 1	PROJECTION		LENGTH	ANGLE	CHECKED BY:		TITLE:	测试探针
DATE:	2013.07.06	VER.	D.0	X.XX ±0.05mm	X.XX ±0.50°	APPROVED BY:			
				X.X ±0.10mm	X.X ±1.00°				
				X. ±0.20mm	X. ±2.00°				