


Note:

- 1: Material (材料):  
 Barrel: PhBz (针管: 磷铜)  
 Plunger A&B: BeCu (针头A&B: 铍铜)  
 Spring: SWP-B (弹簧: 琴钢线SWP-B)
- 2: Plating (电镀):  
 Barrel: 100~140u' Ni plated (针管: 镀镍100~140u'.)  
 Plunger A&B: 40u' Au over 80~120u' Ni (针头A&B: 镀金40u', 镍底80~120u'.)  
 Spring: Gold flash (弹簧: 镀金.)
- 3: Electrical (电气特性):  
 Rated Current: 1.0A (额定电流: 1.0A)  
 Contact Resistance: 100 mohm Max. at working stroke.  
 接触电阻: 最大100毫欧 (在工作行程状态下)
- 4: Mechanical (机械性能):  
 Force: 60g±20% at 3.00mm stroke (60g±20% 在3.00mm行程状态).  
 Full stroke: 3.40mm (全行程: 3.40mm)  
 Durability: 100.000 cycles(min) (寿命: 100000次)



深圳市新富城电子有限公司  
 Xinfucheng Shenzhen Electronics Co., Ltd.  
<http://www.xfcdz.com.cn> TEL: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :		DESIGNED BY:		DWG. NO.	DP4-056317-FB01
SHEET:	1 of 1	PROJECTION		LENGTH	ANGLE	CHECKED BY:		TITLE:	测试探针
DATE:	2013.08.07	VER.	D.0	X.XX ±0.05mm	X.XX ±0.50°	APPROVED BY:			
				X.X ±0.10mm	X.X ±1.00°				
				X. ±0.20mm	X. ±2.00°				