



Note:

- 1: Material:
 Barrel: PhBz
 Plunger: Hardened SK4
 Spring: Music wire
- 2: Plating:
 Barrel: 2u' Au over 50~100u' Ni
 Plunger: 2u' Au over 100~150u' Ni
 Spring: Gold flash.
- 3: Electrical:
 Rated Current: 3A Continuous.
 Contact Resistance: 50 mohm Max. at 2.00 stroke.
- 4: Mechanical:
 Force: 80±24g at 2.00 stroke.
 Full stroke: 3.00mm.
 Durability: 100.000 cycles.
- 5: Work Temperature:
 Withstanding Higt Temperature: 280°C.
 Operational Temperature: - 55°C ~ + 155°C.

物料清单

料件名称	料号
针管	B01-068130-HP
针头	P01-051090-BK
弹簧	S-050088-W10050



深圳市新富城电子有限公司
 Xinfucheng Shenzhen Electronics Co., Ltd.
<http://www.xfcdz.com.cn> TEI: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :				DESIGNED BY:		DWG. NO.	SP1-068170-B01
SHEET:	1 of 1	PROJECTION		LENGTH		ANGLE		CHECKED BY:		TITLE:	测试探针
DATE:	2015.04.16	VER.	D.0	X.XX ±0.05mm	X.XX ±0.50°	X.X ±0.10mm	X.X ±1.00°	APPROVED BY:			
				X. ±0.20mm	X. ±2.00°						