

Note:

1: Material(材料):

Barrel: PhBz C5191 (针管: 磷铜C5191)

Plunger A: SK4 (针头A: SK4)

Plunger B: BeCu C1751 (针头B: 铍铜C1751)

Spring: Music wire SWP-B (弹簧: 琴钢线SWP-B)

2: Plating(电镀):

Barrel: 10u' Au over 80~120u' Ni (针管: 镀金10u', 镍底80~120u'.)

Plunger A&B: 10u' Au over 80~120u' Ni (针头A&B: 镀金10u', 镍底80~120u'.)

Spring: 1u' Au over 50~80u' Ni(弹簧: 镀金1u', 镍底50~80u'.)

3: Electrical(电气特性):

Rated Current & Voltage: DC 12V;0.5A (额定电压&电流: 直流12V,0.5A)


Contact Resistance: 100 mohm Max. at working height.

接触电阻: 最大100毫欧 (在工作高度状态下)

4: Mechanical (机械性能):

Force: 20g±20% at working height. (20g±20% 在工作高度状态下)。

Durability: 200.000 cycles(min) (寿命: 200000次)



深圳市新富城电子有限公司

Xinfucheng Shenzhen Electronics Co., Ltd.

http://www.xfcdz.com.cn TEL: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :		DESIGNED BY:		DWG. NO.	DP1-038058-FB01
SHEET:	1 of 1	PROJECTION		LENGTH	ANGLE	CHECKED BY:		TITLE:	测试探针
DATE:	2013.04.18	VER.	D.0	X.XX ±0.05mm	X.XX ±0.50°	APPROVED BY:			
				X.X ±0.10mm	X.X ±1.00°				
				X. ±0.20mm	X. ±2.00°				