

Note:

1: Material(材料):

Barrel: Brass (针管: 黄铜)

Plunger: SK4 (针头: SK4)

Spring: Music wire SWP-B (弹簧: 琴钢线SWP-B)

2: Plating(电镀):

Barrel: 2u' Au over 80~120u' Ni (针管: 镀金2u', 镍底80~120u'.)

Plunger: 80~120u' Ni plated (针头: 镀镍80~120u'.)

Spring: Gold flash (弹簧: 镀金.)

3: Electrical(电气特性):

Rated Current: 1.5 A (额定电流: 1.5 A)

Contact Resistance: 100 mohm Max. at working stroke.


接触电阻: 最大100毫欧 (在工作行程状态下)

4: Mechanical (机械性能):

Force: 65g±20% at 2.20mm stroke (65g±20% 在2.20mm行程状态)。

Full stroke: 3.35mm (全行程: 3.35mm)

Durability: 200.000 cycles(min) (寿命: 200000次)



深圳市新富城电子有限公司

Xinfucheng Shenzhen Electronics Co., Ltd.

http://www.xfcdz.com.cn TEL: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :		DESIGNED BY:		DWG. NO.	SP1-068163-D01
SHEET:	1 of 1	PROJECTION		LENGTH	ANGLE	CHECKED BY:		TITLE:	测试探针
DATE:	2013.06.29	VER.	D.0	X.XX ±0.05mm	X.XX ±0.50°	APPROVED BY:			
				X.X ±0.10mm	X.X ±1.00°				
				X. ±0.20mm	X. ±2.00°				