


Note:

- 1: Material(材料):
 - Barrel: PhBz (针管: 磷铜)
 - Plunger A&B: BeCu (针头A&B: 铍铜)
 - Spring: Music wire SWP-B (弹簧: 琴钢线SWP-B)
- 2: Plating(电镀):
 - Barrel: 10u' Au over 80~120u' Ni (针管: 镀金10u', 镍底80~120u'.)
 - Plunger A&B: 10u' Au over 80~120u' Ni (针头A&B: 镀金10u', 镍底80~120u'.)
 - Spring: 1u' Au over 50~80u' Ni(弹簧: 镀金1u', 镍底50~80u'.)
- 3: Electrical(电气特性):
 - Rated Current & Voltage: DC 12V;0.5A (额定电压&电流: 直流12V,0.5A)
 - Contact Resistance: 100 mohm Max. at working height.
 - 接触电阻: 最大100毫欧 (在工作高度状态下)
- 4: Mechanical (机械性能):
 - Force: 20g±20% at working height. (20g±20% 在工作高度状态)。
 - Durability: 200.000 cycles(min) (寿命: 200000次)



深圳市新富城电子有限公司
Xinfucheng Shenzhen Electronics Co., Ltd.
http://www.xfcdz.com.cn TEL: 0755-81739711

| | | | | | | | | |
|--------|------------|------------|-----|---------------------------------------|-------------|--------------|----------|-----------------|
| SCALE: | N/A | UNIT | mm | THE UNMARKED TOLERANCE ARE AS BELOW : | | DESIGNED BY: | DWG. NO. | DP1-038058-FB02 |
| SHEET: | 1 of 1 | PROJECTION | | LENGTH | ANGLE | CHECKED BY: | TITLE: | 测试探针 |
| DATE: | 2013.07.25 | VER. | D.0 | X.XX ±0.05mm | X.XX ±0.50° | APPROVED BY: | | |
| | | | | X.X ±0.10mm | X.X ±1.00° | | | |
| | | | | X. ±0.20mm | X. ±2.00° | | | |