



Note:

1: Material(材料):

Barrel: PhBz (针管: 磷铜)

Plunger A&B: BeCu (针头A&B: 铍铜)

Spring: SWP-B (弹簧: 琴钢线SWP-B)

2: Plating(电镀):

Barrel: 20~60u' Au over 60~100u' Ni (针管: 镀金20~60u', 镍底60~100u'.)

Plunger A&B: 40~60u' Au over 80~120u' Ni (针头A&B: 镀金40~60u', 镍底80~120u'.)

Spring: Gold flash (弹簧: 镀金。)

3: Electrical(电气特性):

Rated Current: 0.5A (额定电流: 0.5A)

Contact Resistance: 50 mohm Max. at working stroke.

接触电阻: 最大50毫欧 (在工作行程状态下)

4: Mechanical (机械性能):

Force: 17g±20% at 0.80 mm stroke (17g±20% 在0.80mm行程状态)。

Full stroke: 1.10mm (全行程: 1.10mm)

Durability: 200.000 cycles(min) (寿命: 200000次)



新富城
XINFUCHENG

深圳市新富城电子有限公司

Xinfucheng Shenzhen Electronics Co., Ltd.

http://www.xfcdz.com.cn TEI: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :				DESIGNED BY:		DWG. NO.	DP1-038057-FB01
SHEET:	1 of 1	PROJECTION		LENGTH		ANGLE		CHECKED BY:		TITLE:	测试探针
DATE:	2013.09.05	VER.	D.0	X.XX ±0.05mm	X.XX ±0.50°	X.X ±1.00°	APPROVED BY:				
				X.X ±0.10mm	X. ±2.00°						