




**Tip Style**

F	B	D	G
			

Unit: Millimeter[inch]

 Pointing accuracy:  $\pm 0.04\text{mm}$ 

- **Minimum Pitch:** 0.30mm [.0118]
- **Operating Temperature:**  $-55^{\circ}\text{C}$  to  $+155^{\circ}\text{C}$
- **Mechanical Specifications:**
  - Force: 12g[.4233oz] at 0.60mm[.0236].
  - Recommended stroke: 0.60mm[.0236].
  - Full stroke: 0.90mm[.0354].
  - Mechanical Life: 200,000 cycles.
- **Material and Finishes:**
  - Barrel: Phosphor Bronze /Gold plated
  - Plunger Top: Hardened BeCu /Gold plated
  - Plunger Bottom: Hardened BeCu /Gold plated
  - Spring: Music wire /Gold plated
- **Electrical Specifications:**
  - Rated Current: 0.3A Continuous.
  - Self Inductance: 1.15nH.
  - Bandwidth: 7.45GHz@-1dB.
  - Contact Resistance: Less than 100mohm.
  - Capacitance: 1.38pF.
  - Time Delay: 28 pSec.

All right reserved. No part of this drawing may be copied, reproduced and transmitted in any forms or by any means without written permission of Xinfucheng Shenzhen Electronics Co., Ltd.