


Note:

- 1: Material(材料) :
 - Barrel: PhBz (针管: 磷铜)
 - Plunger A&B: BeCu (针头A&B: 铍铜)
 - Spring: SWP-B (弹簧: 琴钢线SWP-B)
- 2: Plating(电镀) :
 - Barrel: 20~60u' Au over 60~100u' Ni (针管: 镀金20~60u', 镍底60~100u'.)
 - Plunger A&B: 40~60u' Au over 80~120u' Ni (针头A&B: 镀金40~60u', 镍底80~120u'.)
 - Spring: Gold flash (弹簧: 镀金.)
- 3: Electrical(电气特性) :
 - Rated Current: 0.5A (额定电流: 0.5A)
 - Contact Resistance: 50 mohm Max. at working stroke.
接触电阻: 最大50毫欧 (在工作行程状态下)
- 4: Mechanical (机械性能) :
 - Force: 22g±20% at 0.65 mm stroke (22g±20% 在0.65mm行程状态)。
 - Full stroke: 1.10mm (全行程: 1.10mm)
 - Durability: 200.000 cycles(min) (寿命: 200000次)



深圳市新富城电子有限公司
Xinfucheng Shenzhen Electronics Co., Ltd.
http://www.xfcdz.com.cn TEI: 0755-81739711

SCALE:	N/A	UNIT	mm	THE UNMARKED TOLERANCE ARE AS BELOW :		DESIGNED BY:		DWG. NO.	DP1-030067-FF01
SHEET:	1 of 1	PROJECTION		LENGTH	ANGLE	CHECKED BY:		TITLE:	测试探针
DATE:	2013.09.04	VER.	D.0	X.XX ±0.05mm	X.XX ±0.50°	APPROVED BY:			
				X.X ±0.10mm	X.X ±1.00°				
				X. ±0.20mm	X. ±2.00°				